

Pneumatic Speed Adjustment

for UG-5.7/8/10 Lever Governors

Applications

Remote speed adjustment is possible by using this pneumatic speed adjustment unit. It is mounted on top of the UG 5.7, 8, or 10 Lever Governors in a separate housing.

The unit operates on direct air pressure. Level and range adjustments are easily made to match the speed setting of the governor with the air pressure signal.

Required air supply is 3 to 15 psi or 10 to 50 psi. Hysteresis of the speed setting is 0.5%.


The cast aluminum housing accepts solenoid, pneumatic, or low-lube shutdown devices.

Manual Speed Setting

A manual speed setting feature is available as an auxiliary. The screw permits setting speed at the governor. The pneumatic speed setting cannot change the speed of the governor to less than that set on the manual setting.



- Economical
- Positive control
- Separate housing
- Easily adjusted
- Good accuracy



**Outline Drawing of the UG8 Lever Governor
with the Pneumatic Speed Adjustment and Manual Speed Setting Screw**
(Do not use for construction)



PO Box 1519, Fort Collins CO, USA 80522-1519
 1000 East Drake Road, Fort Collins CO 80525
 Tel.: +1 (970) 482-5811 ♦ Fax: +1 (970) 498-3058
www.woodward.com

Distributors & Service

Woodward has an international network of distributors and service facilities. For your nearest representative, call the Fort Collins plant or see the Worldwide Directory on our website.

This document is distributed for informational purposes only. It is not to be construed as creating or becoming part of any Woodward contractual or warranty obligation unless expressly stated in a written sales contract.

© Woodward 1980, All Rights Reserved

For more information contact: