

# SHREDDERS

**“Waste management equipment for the demanding maritime and offshore industry that gets the job done efficiently, safely and in an environmentally responsible manner.”**



DT-230SR, DT-575SR,  
DT-1575SR & DT-190LCS

## KEY BENEFITS

- Stainless steel units for indoor or outdoor placement
- Wheeled, interchangeable stainless steel containers for easy waste segregation and logistics.
- Delitek products are certified by DNV.
- Powerful electric motors for high shaft torque.
- Shredding directly into big bags for easy and safe deployment of waste. (HD plastic bags as alternative for DT-230SR).
- Easy installation and operation (Plug & Play).

**MARINE****OFFSHORE****NAVY****CRUISE****YACHT****FISHING****ONSHORE****DT-230SR**

Material	Stainless steel AISI 304, AISI 316 or painted steel
Capacity	0,2 m <sup>3</sup>
Loading opening (W x H)	635mm x 395mm
Dimensions (W x D x H)	793mm x 1023mm x 1954mm
Weight (Incl. container)	359 Kg
Motor voltage	220/380~440V, 3Ph, 50~60Hz
Motor power	3 kW
Blade size	2mm x 8mm
Shaft torque	1900 Nm
Noise level	<70dB Max

**DT-575SR**

Material	Stainless steel AISI 304 or AISI 316
Capacity	0,5 m <sup>3</sup>
Loading opening (W x H)	695mm x 520mm
Dimensions (W x D x H)	1103mm x 1657mm x 2449mm
Weight (Incl. container)	1311 Kg
Motor voltage	380~440V, 3Ph, 50~60Hz
Motor power	7,5 kW
Blade size	2mm x 12mm
Shaft torque	4580 Nm
Noise level	<70dB Max

**DT-1575SR**

Material	Stainless steel AISI 304 or AISI 316
Capacity	1,5 m <sup>3</sup>
Loading opening (W x H)	695mm x 520mm
Dimensions (W x D x H)	1460mm x 1657mm x 2729mm
Weight (Incl. container)	1415 Kg
Motor voltage	380~440V, 3Ph, 50~60Hz
Motor power	7,5 kW
Blade size	2mm x 12mm
Shaft torque	4580 Nm
Noise level	<70dB Max

**DT-190LCS**

Material	Stainless steel AISI 304 or AISI 316 - PVC Container
Capacity	190 Litre
Loading opening (W x H)	635mm x 395mm
Dimensions (W x D x H)	795mm x 1023mm x 2041mm
Weight (Incl. container)	334 Kg
Motor voltage	220/380~440V, 3Ph, 50~60Hz
Motor power	3 kW
Blade size	2mm x 8mm
Shaft torque	1900 Nm
Noise level	<70dB Max

All specifications are subject to change without notice.

**Delitek AS (Head Office)**

Molveien 1 N-8432 Alsvåg, Norway Tel: +47 76 18 57 60 Fax: +47 76 13 42 77 e-mail: sales@delitek.no  
[www.delitek.no](http://www.delitek.no)